



## SEMI ELECTRICAL STACKER

MODEL		LSE1T*1.6	LSE1T*3	LSE1.5T*3/ LSE1.5T*3.5
Capacity	KG	1000	1000	1500
Load Centre	(mm) – C	450	450	450
Min. Fork Height	(mm) – H1	90	90	90
Max. Fork Height	(mm) – H2	1600	3000	3000/3500
Fork outside width	(mm) – E	320-710	320-710	320-710
Fork inside width	(mm)	20-410	20-410	20-410
Fork Length	(mm) – L1	1000	1000	1000
Single Fork Size	(mm) – e/s	150/60	150/60	150/60
Overall Length	(mm) – L	1660	1660	1660
Overall Width	(mm) – B	770	770	770
Overall Height	(mm) – H	2130	2080	2130
Max. Lifting Height	(mm)	1510	2910	2910
Min. Turning Radius	(mm) – Wa	1350	1350	1450
Lifting Speed	(mm/s)	40-50/85-95	40-50/85-95	40-50/85-95
Lowering Speed	(mm/s)	90-110/85-95	90-110/85-95	90-110/85-95
Lift Motor	Kw	1.6	1.6	1.6
Battery Capacity	V/Ah	12V/120Ah	12V/120Ah	12V/120Ah
Battery Weight	KG	36	36	36
Net Weight	KG	340	430	450/465