

# ELECTRICAL CHAIN BLOCK WITH TROLLEY INTEGRATED MODEL

MODEL	CAPACITY TON	STANDARD LIFT (MTR)	TEST LOAD (KN)	MOTOR POWER (KW)	IP RATINGS & VOLTS	NO. OF CHAIN	DIA OF CHAIN (MM)	LIFTING SPEED (M/MIN)	NET WEIGHT (KG)
LECBT0.5	0.5	6	6.25	0.75	IP54 380V	1	6.3	6.9	89
LECBT1	1	6	12.5	1.5		1	7.1	6.9	103
LECBT2	2	6	25	3.0		2	7.1	6.8	164
LECBT3	3	6	37.5	3.0		1	11.2	5.4	183
LECBT5	5.0	6	62.5	3.0		2	11.2	2.7	234
LECBT7.5	7.5	6	94	3.0		3	11.2	1.8	266
LECBT10	10.0	6	125	3.0		4	11.2	2.7	335
LECBT20	20.0	6	250	3.0		8	11.2	1.5	546

MODEL	CAPACITY (TON)	H	A	B	D	E	I	J	K	L	M	N	P	Q	R	T	I-BEAM SIZE
		MM	MM	MM	MM	MM	MM	MM	MM	MM	MM	MM	MM	MM	MM	MM	MM
LECBT0.5	0.50	440	460	230	/	/	31	31	35	25	25	17	206	111	142	231	58-153
LECBT1	1.0	480	520	260	/	/	31	31	40	31	31	22	206	111	142	231	58-153
LECBT2	2.0	535	615	295	/	/	31	31	36	47	38	30	237	127	142	231	82-178
LECBT3	3.0	685	615	295	/	/	36	43	58	47	47	36	265	140	142	231	100-178
LECBT5	5.0	740	615	295	/	/	43	54	60	48	48	43	296	156	142	231	100-178
LECBT7.5	7.5	890	615	295	/	/	43	54	85	80	80	53	296	156	142	231	100-178
LECBT10	10.0	880	630	315	1640	820	54	54	85	80	80	55	366	191	142	231	150-220
LECBT20	20	1470	630	315	1260	630	70	54	150	115	80	98	1106	740	142	231	150-220