

MOBILE SCISSOR LIFT PLATFORM



This equipment is designed to reach greater heights while maintaining user's flexibility, convenience and safety. Generally used for temporary, flexible access purposes such as maintenance and construction work. Also suitable for multi-layer workshops, warehouses, production lines and transporting goods with different heights.

It provides excellent maneuverability in tight spaces. A safe and efficient solution for working at height.



TECHNICAL SPECIFICATIONS		
Product Code	LMEL0339	
Lift Rated Capacity	kg	300
MAX Working Height	mm	5900
MAX Platform Height	mm	3900
Overall Length	mm	1180
Overall Width	mm	760
Overall Height	mm	1930
Platform Size	mm	1170x600
Ground Clearance	mm	60
Wheel Base	mm	990
MIN Turning Radius	mm	1200
Driving Motor	V/kW	2x24/0.4
Lifting Motor	V/kW	24/0.8
Running Speed (Platform Stowed)	km/h	4
Running Speed (Platform Elevated)	km/h	0.8
Rising/Falling Speed	sec	20/30
Battery	V/Ah	2x12/60
Charger	V/Ah	24/10
MAX Climbing Ability	%	10-15
MAX Working Allowable Angle	/	2°
Driving Wheel Diameter	mm	230x80
Front Wheel Diameter	mm	150x60
Overall Net Weight	kg	600